

Note: technical drawings are not to scale

reversible window **DOUBLE GLAZED SPECIFICATION**

PROFILES

– Eurocell reversible system

REINFORCEMENTS

– Steel

CILL OPTIONS


Standard: 85mm (130mm*), 150mm (195mm*) and 180mm (225mm*)

* When used with cill extender

ACCREDITATIONS

– BS EN 12608, BS 7412, BS 6375, BS 7950

STYLE



Chamfered

THERMAL PERFORMANCE

System	Config	Glass 1 (external)	Glass 2 (internal)	Gas fill	Spacer bar	Reinforcing	WER	Energy Index	U Value
reversible	4/20/4	SG Diamant	SG Planitherm Total Plus	Argon	Swisspacer V	Full steel		-14	1.5
reversible	4/20/4	Float	SG Planitherm Total Plus	Argon	Superspacer	Full steel		-15	1.5
reversible	4/20/4	Pilkington Optiwhite	Pilkington K	Argon	Superspacer	Full steel		-18	1.7
reversible	4/20/4	Pilkington Optiwhite	Pilkington K OW	Argon	Superspacer	Full steel		-18	1.7

COLOUR OPTIONS

Standard colours



Non-standard options

Eurocell profiles are available in any colour from our made-to-order range. These are available on a three-week lead-time.

MIN /MAX WINDOW SIZES

If the windows are to be manufactured outside these sizes, please consult Eurocell's technical department.

System	Width (mm)	Height (mm)
Reversible windows	Max sash weight 60kg	Width must not exceed height